

Wire Rope Cutters





This can cut dia. 20mm (3/4") Steel Core Wire rope, IWRC 6 X Fi(29)



Cutting Speed: 4seconds



☐ Double insulation

Size: 420mm(W) X 104mm(D) X 216mm(H)

Wire rope cutter RC-450

Cutting capacity dia. 12mm(1/2") fiber core wire rope



Carry Case



Shoulder Strap

Cordless WRC20-MH230 Cordless Wire Rope Cutters (Hydraulic function

Cutting Speed: 7seconds

Battery Output: 14.4V



WRC20-MH230

Size: 350mm(W) X 90mm(D) X 340mm(H)

y charged	

WRC20-MH120 / WRC20-MH230 Dia.20mm(3/4") 60 times Fiber core wire rope

Carry Case



Nickel-Metal Hydride Battery (Ni-MH) DC14.4V







Battery charger AC230V



Shoulder Strap

Wire rope cutter RC-450

Cutting capacity dia. 12mm(1/2") fiber core wire rope



Spare Products		
Product Name	Item No.	Weight
Nickel-Metal Hydride Battery	EB1430R	0.8kg
Battery charger 【120V】	UC18YRL	0.7kg
Battery charger [230V]	UC24YC	1.2kg

Cutting Wire Rope



Blades

Battery charger

Powder high speed steel with Titanium coating.

Output pressure

Safety-valve will be automatically operated, when the pressure is over 10tonf.

Head turns around

Head turns 180 degrees.

	Item No.	Electrical input	Electricity	Cutting Capacity dia. mm (inch)	Weight	Packing weight	M 3
Elec	WRC20-120V	AC120V	7.0A	20 (3/4")	7.1kg	13kg	0.056
	WRC20-230V	AC230V	3.6A	20 (3/4)			
Cord	Item No.	Battery / Electrical input	Charging time	Cutting Capacity dia. mm (inch)	Weight	Packing weight	M 3
	WRC20-MH120	14.4V 3000mAh(Ni-MH) / AC120V	45 minutes	20 (3/4")	6.3kg	14.3kg	0.063
	WRC20-MH230	14.4V 3000mAh(Ni-MH) / AC230V	37 minutes	20 (3/4)			